

Totally Enclosed Free Fall Lifeboat GES-18



 SOLAS
approved

Product code: 1310105100

Totally Enclosed Free Fall Lifeboat VIKING Norsafe GES-18 provides a secure and protected means of escape for persons onboard vessels or platforms and is for skid launch by a specific davit.

The self-righting lifeboat, If damaged below the waterline, has enough buoyancy to stay at sea surface. Embarkation is through the aft door. Seats are positioned on each side of the central aisle.

The lifeboat is equipped with mechanical steering. Additional types of boats are available upon prior request.

It is designed and manufactured according to latest SOLAS requirements.



Key features:

- Rapid evacuation time from muster point to water entry;
- Free-fall launch will move the boat to a safe location, away from the platform;
- Simulated release systems to allow unmanned launch drill without free-fall launch;
- This boat can be delivered as Tanker/ Offshore or Dry Cargo version;



Totally Enclosed Free Fall Lifeboat GES-18



SOLAS
approved

Boat specifications:

- Length overall - 5,06 m;
- Beam - 2,20 m;
- Height - 3,10 m;
- Maximum installation height [m] – 15,0 m;
- Launching ramp length and angle – 6 m, 35°;
- Capacity, SOLAS - maximum 18 persons;
- Weight, fully equipped - 3.265 kg;
- Davit load, with 18 pers. = 4.750 kg;
- External Color - Orange (RAL 2004);
- Internal Color - Light Gray (RAL 7032);
- Operation temperature - from -15°C to +40°C;
- Hull/deck material - fire retardant glass reinforced polyester;
- Buoyancy material - polyurethane foam;
- Windows - polycarbonate;
- Bollards/towing - aft bollard port and starboard side, bollard in bow;
- Steering - mechanical;
- Hatches – 1 aft door / 1 top hatch / 1 front top hatch;
- Seat belt type – 4-point adjustable seat harness;

Product code: 1310105100